

G25WDO-3A-T4F

The G25 from Doosan Portable Power is dependable power in a small package. The G25 features Tier 4 final-compliant technology and Doosan Portable Power's legendary rugged enclosure and running gear, ensuring impressive performance regardless of jobsite conditions. The user-friendly controls, 25-hour run time, and sound attenuation make the G25 ideal for events, emergency backups, and construction.



Prime Output
25 kVA (20 kW)

Sound Level (100% Load)
63 dB(A)

Engine
Doosan D18

Specifications

Prime Power Rating

@ 480V-3Ø, 0.8PF, 60Hz	25 kVA (20 kW), 30 Amps
@ 240V-3Ø, 0.8PF, 60Hz	25 kVA (20 kW), 60 Amps
@ 208V-3Ø, 0.8PF, 60Hz	22 kVA (17 kW), 61 Amps
@ 240V-1Ø, 1.0PF, 60Hz	16.5 kVA (16.5 kW), 69 Amps
↻ 120V-1Ø, 1.0PF, 60Hz	16.5 kVA (16.5 kW), 69 x 2 Amps
↻ 400V-3Ø, 0.8PF, 50Hz	20 kVA (16 kW), 29 Amps
Voltage Configuration	3-Position Switch
Frequency Capability	50Hz/60Hz Switchable

FEEDBACK

Engine

Make/Model	Doosan D18
Displacement (L)	1.794

Number of Cylinders	3
Power Output @ 1800RPM - HP (kWm)	33.5 (25)
Emissions Tier Level	Tier 4 Final
Aftertreatment Technology	DOC
Fuel Tank Capacity - Gal (L)	47 (177)
Diesel Exhaust Fluid (DEF) Capacity - Gal (L)	N/A
Runtime @ 100% Load - Hr	25.9

Dimensions With Running Gear

Length - in (mm)	130.5 (3315)
Width - in (mm)	72.8 (1850)
Height - in (mm)	76.6 (1946)
Weight (Ready to Run) - lb (kg)	3140 (1424)
Sound Level @ 23 ft (7m) and 100% Load - dB(A)	63

